

Molded Case Circuit Breakers

BQ 125A Frame

Selection

Ordering Instructions

- All BQ circuit breakers are supplied with load side lugs. If line side lugs are required, add suffix 'L' to catalog number. Lugs will be supplied at no charge if ordered with circuit breakers. All standard circuit breakers are calibrated for 40°C maximum ambient application.

BQ 125A Frame — BQ (10,000A IR)^②

Non-Interchangeable Trip

Continuous Current Rating @ 40° C	1-Pole		2-Pole		2-Pole		3-Pole	
	120/240V AC		120/240V AC Common Trip		240V AC Common Trip ^⑤		240V AC Common Trip	
	Catalog Number	List Price \$	Catalog Number	List Price \$	Catalog Number	List Price \$	Catalog Number	List Price \$
15	BQ1B015 ^{①②③}		BQ2B015 ^⑤		BQ2H015 ^⑤		BQ3B015 ^⑤	
20	BQ1B020 ^{①②③}		BQ2B020 ^⑤		BQ2H020 ^⑤ ■		BQ3B020 ^⑤	
25	BQ1B025 ^{②③}		BQ2B025 ^⑤		—		BQ3B025 ^⑤	
30	BQ1B030 ^{②③}		BQ2B030 ^⑤		BQ2H030 ^⑤ ■		BQ3B030 ^⑤	
35	BQ1B035 ^{②⑤} ■		BQ2B035 ^⑤		—		BQ3B035 ^⑤	
40	BQ1B040 ^{②⑤}		BQ2B040 ^⑤		BQ2H040 ^⑤ ■		BQ3B040 ^⑤	
45	BQ1B045 ^{②⑤} ■		BQ2B045 ^⑤ ■		—		BQ3B045 ^⑤	
50	BQ1B050 ^{②⑤}		BQ2B050 ^⑤		BQ2H050 ^⑤ ■		BQ3B050 ^⑤	
55	BQ1B055 ^{②⑤} ■		—		—		—	
60	BQ1B060 ^{②⑤}		BQ2B060 ^⑤		BQ2H060 ^⑤ ■		BQ3B060 ^⑤	
70	BQ1B070 ^⑤		BQ2B070 ^⑤		BQ2H070 ^⑤ ■		BQ3B070 ^⑤	
80			BQ2B080 ^⑤		—		BQ3B080 ^⑤	
90			BQ2B090 ^⑤		BQ2H090 ^⑤ ■		BQ3B090 ^⑤	
100			BQ2B100 ^⑤		BQ2H100 ^⑤ ■		BQ3B100 ^⑤	
110			BQ2B110					
125			BQ2B125					

BQH (22,000A IR)^②

15	BQ1B015H ^①		BQ2B015H		—		BQ3B015H	
20	BQ1B020H ^①		BQ2B020H		—		BQ3B020H	
30	BQ1B030H		BQ2B030H		—		BQ3B030H	
40	BQ1B040H■		BQ2B040H		—		BQ3B040H	
50	BQ1B050H■		BQ2B050H		—		BQ3B050H	
55	BQ1B055H■		—		—		—	
60	BQ1B060H■		BQ2B060H		—		BQ3B060H	
70	BQ1B070H■		BQ2B070H		—		BQ3B070H■	
80			BQ2B080H		—		BQ3B080H■	
90			BQ2B090H		—		BQ3B090H■	
100			BQ2B100H		—		BQ3B100H	
125			BQ2B125H■		—		—	

HBQ (65,000A IR)^②

15	HB1B015 ^①		HB2B015■		—		HB3B015■	
20	HB1B020 ^①		HB2B020■		—		HB3B020■	
30	HB1B030■		HB2B030■		—		HB3B030■	
40	HB1B040■		HB2B040■		—		HB3B040■	
50	HB1B050■		HB2B050■		—		HB3B050■	
60	—		HB2B060■		—		HB3B060■	
70	—		HB2B070■		—		HB3B070■	
80	—		—		—		HB3B080■	
90	—		HB2B090■		—		HB3B090■	
100	—		HB2B100■		—		HB3B100	

BQ/BQH/HBQ

Internal Accessories (Factory installed only)

Control Voltage		Shunt Trip		Auxiliary Switches	
				1A and 1B	
AC	DC	Suffix	List Adder \$	Suffix	List Adder \$
120V		...00S01■		...A01■	

■ Built to order. Allow 2-3 weeks for delivery.

①UL Listed for frequent switching applications (SWD).
120V AC fluorescent lighting.

②HCAR rated.

③For 400 cycle UL Listed devices, add "Y" suffix to catalog number. The list price will be increased 25% for 400 Hz.
5000A interrupting rating.■

④UL Listed for use on 3 phase grounded "B" systems—
5000A IR for this application.

Interrupting Ratings page 11/5
Accessories pages 11/67 to 11/72
Modifications page 11/65