



# Molded Case Circuit Breakers

Selection

Magnetic Trip Only — ETI Motor Circuit Protector

16

Molded Case  
Circuit Breakers

Breaker Type	Ampere Rating	Instantaneous Trip Range <sup>③</sup>		Complete Circuit Breaker With Lugs				
		Minimum <sup>③</sup>	Maximum <sup>③</sup>	Catalog Number 2-Pole	List Price <sup>④</sup>	Catalog Number 3-Pole	List Price <sup>④</sup>	
ED6-A 600V AC 250V DC	1	2.6	9	—	—	ED63A001		
	2	7	22	—	—	ED63A002		
	3	10	35	—	—	ED63A003		
	5	16	54	—	—	ED63A005		
	10	30	100	—	—	ED63A010		
	25	55	180	—	—	ED63A025		
	30	80	270	—	—	ED63A030		
	40	115	375	—	—	ED63A040		
	50	180	600	—	—	ED63A050		
	100	315	1000	—	—	ED63A100		
	125	500	1250	—	—	ED63A125		
	SHIPPING:						3.8 lbs. each	
	CED6-A 600V AC 250V DC	1	2.6	9	—	—	CED63A001	
2		7	22	—	—	CED63A002		
3		10	35	—	—	CED63A003		
5		16	54	—	—	CED63A005		
10		30	100	—	—	CED63A010		
25		55	180	—	—	CED63A025		
30		80	270	—	—	CED63A030		
40		115	375	—	—	CED63A040		
50		180	600	—	—	CED63A050		
100		315	1000	—	—	CED63A100		
125		500	1250	—	—	CED63A125		
SHIPPING:						6 lbs. each		
FXD6 <sup>①</sup> 600V AC 250V DC		150	400	800	FXD62L150		FXD63L150	
	150	800	1500	FXD62A150		FXD63A150		
	150	1100	2500	FXD62H150		FXD63H150		
	250	1100	2500	FXD62A250		FXD63A250		
	SHIPPING:						7 lbs. each 9 lbs. each	
CFD6 <sup>①</sup> 600V AC 250V DC	150	400	800	CFD62L150		CFD63L150		
	150	800	1500	CFD62A150		CFD63A150		
	150	1100	2500	CFD62H150		CFD63H150		
	250	1100	2500	CFD62A250		CFD63A250		
	SHIPPING:						12 lbs. each 12 lbs. each	
JXD6(A) <sup>①</sup> 600V AC 250V DC	400	1250	2500	JXD62L400		JXD63L400		
	400	2000	4000	JXD62H400		JXD63H400		
	SHIPPING:						16 lbs. each 20 lbs. each	
CJD6 <sup>①</sup> 600V AC 250V DC	400	1250	2500	CJD62L400		CJD63L400		
	400	2000	4000	CJD62H400		CJD63H400		
	SHIPPING:						29.5 lbs. each 31.5 lbs. each	
LXD6(A) <sup>①</sup> 600V AC 250V DC	600	2000	4000	LXD62L600		LXD63L600		
	600	3000	6000	LXD62H600		LXD63H600		
	SHIPPING:						16 lbs. each 20 lbs. each	
CLD6 <sup>①</sup> 600V AC 250V DC	600	2000	4000	CLD62L600		CLD63L600		
	600	3000	6000	CLD62H600		CLD63H600		
	SHIPPING:						29.5 lbs. each 31.5 lbs. each	
LMXD6 <sup>①</sup> 600V AC 250V DC	800	2800	6000	LMXD62L800		LMXD63L800		
	800	3200	8000	LMXD62A800		LMXD63A800		
	SHIPPING:						35 lbs. each 35 lbs. each	
MXD6 <sup>①</sup> 600V AC 250V DC	800	3000	6000	MXD62L800		MXD63L800		
	800	4000	8000	MXD62A800		MXD63A800		
	800	5000	10000	MXD62H800		MXD63H800		
	SHIPPING:						27 lbs. each 33 lbs. each	
CMD6 <sup>①</sup> 600V AC 250V DC	800	3000	6000	CMD62L800		CMD63L800		
	800	4000	8000	CMD62A800		CMD63A800		
	800	5000	10000	CMD62H800		CMD63H800		
	SHIPPING:						80 lbs. each 80 lbs. each	

### Important Information

ETI interrupting ratings are determined through combination tests with properly sized overload relays and contactors.

**Connectors included when ordering by circuit breaker catalog number for ED6 and CED6 ETI's. Order ETI circuit breaker and lugs (2 per pole) separately for the FXD6, CFD6, MD6, CMD6, JXD6, CJD6, LXD6 and CLD6 ETI's.**

① 2-pole available in 3-pole width only.

② When applied on DC Circuits — Trip levels will increase approximately +15 to 20%.

③ Tolerance -20/+30%

④ Consult sales office for prices.

Lug Information pages 854-856  
Accessories pages 858-872

Built to order. Allow 2 weeks for production.