



MAL/MHL 2P and 3P
300–1000 A

Table 11.55: M-Frame—Thermal-Magnetic, Individually-Mounted Circuit Breakers, 600 Vac

Ampere Rating	AC Magnetic Trip Settings▲		Standard Interrupting		High Interrupting		Terminal Wire Range
	Low	High	Cat. No.	\$ Price	Cat. No.	\$ Price	
2P, 600 Vac, 250 Vdc							
300 A	1500 A	3000 A	MAL26300	5960.00	MHL26300	7829.00	AL900MA (3) 3/0 AWG–500 kcmil
350 A	1750 A	3500 A	MAL26350	5960.00	MHL26350	7829.00	
400 A	2000 A	4000 A	MAL26400	5960.00	MHL26400	7829.00	
450 A	2250 A	4500 A	MAL26450	5960.00	MHL26450	7829.00	
500 A	2500 A	5000 A	MAL26500	5960.00	MHL26500	7829.00	
600 A	3000 A	6000 A	MAL26600	5960.00	MHL26600	7829.00	
700 A	3500 A	7000 A	MAL26700	7719.00	MHL26700	9657.00	
800 A	4000 A	8000 A	MAL26800	7719.00	MHL26800	9657.00	
900 A	4500 A	9000 A	MAL26900	11012.00	MHL26900	12212.00	
1000 A	5000 A	10000 A	MAL261000	11012.00	MHL261000	12212.00	
1200 A	5000 A	10000 A	MAL261200	12948.00	MHL261200	15252.00	
3P, 600 Vac, 250 Vdc							
300 A	1500 A	3000 A	MAL36300	7560.00	MHL36300	9456.00	AL900MA (3) 3/0 AWG–500 kcmil
350 A	1750 A	3500 A	MAL36350	7560.00	MHL36350	9456.00	
400 A	2000 A	4000 A	MAL36400	7560.00	MHL36400	9456.00	
450 A	2250 A	4500 A	MAL36450	7560.00	MHL36450	9456.00	
500 A	2500 A	5000 A	MAL36500	7560.00	MHL36500	9456.00	
600 A	3000 A	6000 A	MAL36600	9927.00	MHL36600	9456.00	
700 A	3500 A	7000 A	MAL36700	9927.00	MHL36700	11882.00	
800 A	4000 A	8000 A	MAL36800	12705.00	MHL36800	11882.00	
900 A	4500 A	9000 A	MAL36900	12705.00	MHL36900	14078.00	
1000 A	5000 A	10000 A	MAL361000	12705.00	MHL361000	14078.00	
1200 A	5000 A	10000 A	MAL361200	15107.00	MHL361200	17612.00	

- ▲ UL magnetic trip setting tolerances are ±25% for low and ±20% for high from nominal values shown.
- The AL100MA lug is the only lug available for the 1200 A MA and MH circuit breakers.

Table 11.56: M-Frame—Thermal-Magnetic, I-Line® Construction Circuit Breakers, 600 Vac

Ampere Rating	AC Magnetic Trip Settings♦		Standard Interrupting		High Interrupting		Terminal Wire Range
	Low	High	Cat. No.	\$ Price	Cat. No.	\$ Price	
2P, 600 Vac, 250 Vdc★							
300 A	1500 A	3000 A	MA26300()	6633.00	MH26300()	8253.00	AL900MA (3) 3/0 AWG–500 kcmil
350 A	1750 A	3500 A	MA26350()	6633.00	MH26350()	8253.00	
400 A	2000 A	4000 A	MA26400()	6633.00	MH26400()	8253.00	
450 A	2250 A	4500 A	MA26450()	6633.00	MH26450()	8253.00	
500 A	2500 A	5000 A	MA26500()	6633.00	MH26500()	8253.00	
600 A	3000 A	6000 A	MA26600()	6633.00	MH26600()	8253.00	
700 A	3500 A	7000 A	MA26700()	8370.00	MH26700()	10104.00	
800 A	4000 A	8000 A	MA26800()	8370.00	MH26800()	10104.00	
3P, 600 Vac, 250 Vdc							
300 A	1500 A	3000 A	MA36300	8168.00	MH36300	9929.00	AL900MA (3) 3/0 AWG–500 kcmil
350 A	1750 A	3500 A	MA36350	8168.00	MH36350	9929.00	
400 A	2000 A	4000 A	MA36400	8168.00	MH36400	9929.00	
450 A	2250 A	4500 A	MA36450	8168.00	MH36450	9929.00	
500 A	2500 A	5000 A	MA36500	8168.00	MH36500	9929.00	
600 A	3000 A	6000 A	MA36600	8168.00	MH36600	9929.00	
700 A	3500 A	7000 A	MA36700	10608.00	MH36700	12630.00	
800 A	4000 A	8000 A	MA36800	10608.00	MH36800	12630.00	

- ♦ UL magnetic trip setting tolerances are ±25% for low and ±20% for high from nominal values shown.
- ★ 2P circuit breaker catalog numbers are completed by adding required phase connection letters as suffix to catalog numbers. See Phase Options table.

Table 11.57: Interrupting Ratings

Voltage	MA/MAL	MH/MHL
240 Vac	42 kA	65 kA
480 Vac	30 kA	65 kA
600 Vac	22 kA	25 kA

Table 11.58: Phase Options

Phase Option Letter	2P	3P
AB	MA26800AB	
AC	MA26800AC	
BC	MA26800BC	
ABC		MA36800
CBA		MA36800CBA

Accessories Page 11-30
 Optional Lugs Page 11-25
 Dimensions Page 11-4
 Enclosures: see Digest Section 7

OBSOLETE CIRCUIT BREAKERS