

GE OEM Load Center Parts Program

Q Line Circuit Breakers

Standard Circuit Breakers

- UL Listed (Molded-Case Circuit Breakers No. 489)
- Federal Government Specification Qualified (WC-375B)
- 60°/75° C Conductor Rating
- Quick-Make, Quick-Break
- Box-Type Terminals

Breaker-Type	Ampere-Rating	Wire-Size-AWG/ kcmil	
		Cu	Al
THQP	15-25	14-8	12-8
	30-50	8-4	8-2
THQL THHQL TXQL	15-30	14-8	12-8
	35-60	8-3	8-2
	70-100	6-1/0	4-1/0
	110-125	2-2/0	2-2/0
TQDL THQDL	125-200	1/0-250	1/0-250

Ampere Rating	10,000-AIC			22,000-AIC		65,000-AIC
	Type-THQP- 1/2" Module	Type-THQL-1" Module		Type-THHQL-1" Module		Type-TXQL-1" Module
	120/240- Vac	240- Vac	120/240- Vac	240- Vac	120/240- Vac	120/240- Vac
	Cat.-No.	Cat.-No.	Cat.-No.	Cat.-No.	Cat.-No.	Cat.-No.
Single-Pole ①						
15②	THQP115	THQL1115	—	THHQL1115	—	TXQL1115
20②	THQP120	THQL1120	—	THHQL1120	—	TXQL1120
25	THQP125	THQL1125	—	THHQL1125	—	TXQL1125
30	THQP130	THQL1130	—	THHQL1130	—	TXQL1130
35	THQP135	THQL1135	—	THHQL1135	—	—
40	THQP140	THQL1140	—	THHQL1140	—	—
45	THQP145	THQL1145	—	THHQL1145	—	—
50	THQP150	THQL1150	—	THHQL1150	—	—
Std. Pkg.	5 cartons of 20	5 cartons of 10	—	5 cartons of 10	—	5 cartons of 10
Two-Pole ③ :-Incorporates-Internal-Common-Trip-Bar						
15	THQP215	THQL2115	THQL2215	THHQL2115	THHQL2215	TXQL2115
20	THQP220	THQL2120	THQL2220	THHQL2120	THHQL2220	TXQL2120
25	THQP225	THQL2125	THQL2225	THHQL2125	THHQL2225	TXQL2125
30	THQP230	THQL2130	THQL2230	THHQL2130	THHQL2230	TXQL2130
35	THQP235	THQL2135	THQL2235	THHQL2135	THHQL2235	—
40	THQP240	THQL2140	THQL2240	THHQL2140	THHQL2240	—
45	THQP245	THQL2145	THQL2245	THHQL2145	THHQL2245	—
50	THQP250	THQL2150	THQL2250	THHQL2150	THHQL2250	—
60	—	THQL2160	THQL2260	THHQL2160	THHQL2260	—
70	—	THQL2170	THQL2270	THHQL2170	THHQL2270	—
80	—	THQL2180	THQL2280	THHQL2180	THHQL2280	—
90	—	THQL2190	THQL2290	THHQL2190	THHQL2290	—
100	—	THQL21100	THQL22100	THHQL21100	THHQL22100	—
110	—	THQL21110	—	THHQL21110	—	—
125	—	THQL21125	—	THHQL21125	—	—
Std. Pkg.	5 cartons of 10	5 cartons of 5	5 cartons of 5	5 cartons of 5	5 cartons of 5	5 cartons of 5
125	—	TQDL21125④	—	THQDL21125④	—	—
150	—	TQDL21150④	—	THQDL21150④	—	—
175	—	TQDL21175④	—	THQDL21175④	—	—
200	—	TQDL21200④	—	THQDL21200④	—	—
Std. Pkg.	—	10 cartons of 1	—	10 cartons of 1	—	—
Three-Pole ③ :-Incorporates-Internal-Common-Trip-Bar						
15	—	—	THQL32015	—	THHQL32015	TXQL32015
20	—	—	THQL32020	—	THHQL32020	TXQL32020
25	—	—	THQL32025	—	THHQL32025	TXQL32025
30	—	—	THQL32030	—	THHQL32030	TXQL32030
35	—	—	THQL32035	—	THHQL32035	—
40	—	—	THQL32040	—	THHQL32040	—
45	—	—	THQL32045	—	THHQL32045	—
50	—	—	THQL32050	—	THHQL32050	—
60	—	—	THQL32060	—	THHQL32060	—
70	—	—	THQL32070	—	THHQL32070	—
80	—	—	THQL32080	—	THHQL32080	—
90	—	—	THQL32090	—	THHQL32090	—
100	—	—	THQL32100	—	THHQL32100	—
Std. Pkg.	—	—	5 cartons of 3	—	5 cartons of 3	5 cartons of 3

① UL Listed as HACR (heating, air conditioning, and refrigeration).

② UL Listed as SWD (switching duty). Suitable for 120 volts ac fluorescent lighting loads.

③ 15-100 A UL Listed as HACR (heating, air conditioning, and refrigeration.).

④ Requires four 1-inch spaces.